

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025	Product code: 7418		Page 1 of 13					
SECTION 1: Identification of the substance/mixture and of the company/undertaking								
<u>1.1. Product identifier</u> Kisling - 7418 - Component A 74	420							
UFI:	FVHN-P0V0-X00F-RHKJ							
	ubstance or mixture and uses advised agai	Inst						
Use of the substance/mixture Adhesives and sealants								
Uses advised against								
No information available.								
1.3. Details of the supplier of the safe	ety data sheet							
Manufacturer								
Company name:	Kisling AG							
Street:	Motorenstrasse 102							
Place:	CH-8620 Wetzikon							
Telephone:	+41 58 272 0 272							
E-mail:	customerservice@kisling.com							
Contact person:	Product Compliance	Telephone: +49 7940 5096 143						
E-mail:	compliance@kisling.com	·						
Internet:	www.kisling.com							
Supplier								
Company name:	Kisling (Deutschland) GmbH							
Street:	Salzstraße 15							
Place:	D-74676 Niedernhall							
Telephone:	+49 7940 50961 61							
E-mail:	customerservice@kisling.com							
Contact person:	Product Compliance	Telephone: +49 7940 5096 143						
E-mail:	compliance@kisling.com	· · · · · · · · · · · · · · · · · · ·						
Internet:	www.kisling.com							
1.4. Emergency telephone	24 hr. emergency phone number +1 872 5	888271 (KAR)						
number:	Medicines & Poisons Info Office +356 254							

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)

Signal word: Warning



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420 Revision date: 21.03.2025 Product code: 7418 Page 2 of 13 **Pictograms:** Hazard statements H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. P280 Wear protective gloves and eye protection/face protection. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. Labelling of packages where the contents do not exceed 125 ml Warning Signal word: **Pictograms:** Hazard statements H317 **Precautionary statements** P261-P280-P333+P313-P362+P364 2.3. Other hazards No data available **SECTION 3: Composition/information on ingredients**

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
1675-54-3	-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			50 - < 100 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1, Aquatic Chronic 2; H315 H319 H3	17 H411	
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)			15 - < 30 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1; H315 H319 H317		

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	50 - < 100 %
	dermal: LD50 = Irrit. 2; H319: >	= 23000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye = 5 - 100	
25068-38-6		4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)	15 - < 30 %
	dermal: LD50 =	= >2000 mg/kg; oral: LD50 = >2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 4 of 13

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place. Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent					
DNEL type		Exposure route	Effect	Value		
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]	bisoxirane				
Worker DNEL,	long-term	inhalation	systemic	4,93 mg/m³		
Worker DNEL,	long-term	dermal	systemic	0,75 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	0,87 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	0,0893 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	0,5 mg/kg bw/day		
Consumer DN	EL, acute	oral	systemic	0,5 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 5 of 13

PNEC values

CAS No	Name of agent				
Environmenta	Environmental compartment Value				
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane				
Freshwater		0,006 mg/l			
Freshwater (i	Freshwater (intermittent releases) 0,018 mg/l				
Marine water	0,001 mg/l				
Freshwater sediment 0,341 mg/kg					
Marine sediment 0,034 mg					
Secondary poisoning 11 mg					
Micro-organis	Micro-organisms in sewage treatment plants (STP)				
Soil		0,065 mg/kg			

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

EN ISO 374

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	light yellow
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point: Boiling point or initial boiling point and boiling range: Test method

not determined not determined

M - en



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420					
Revision date: 21.03.2025	Product code: 7418	Page 6 of 13			
Flammability:	not determined	not applicable			
Lower explosion limits:	not determined				
Upper explosion limits:	not determined				
Flash point:	>100 °C				
Auto-ignition temperature:	not determined				
Decomposition temperature:	not determined				
pH-Value:	not determined				
Viscosity / kinematic:	not determined				
Water solubility:	practically insoluble				
Solubility in other solvents not determined					
Partition coefficient n-octanol/water:	not determined				
Vapour pressure:	not determined				
Density (at 20 °C):	1.17 g/cm³				
Relative density:	not determined				
Relative vapour density:	not determined				
9.2. Other information					
Information with regard to physical hazard classes Explosive properties					
The product is not: Explosive. not explosive.					
Oxidizing properties not determined					
Other safety characteristics					
Evaporation rate:	not determined				
Solid content:	not determined				
Viscosity / dynamic:	not determined				

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours. Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 7 of 13

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

aust/mist) > 5 m

CAS No	Chemical name	Chemical name				
	Exposure route	Dose		Species	Source	Method
1675-54-3	2,2'-[(1-methylethylidene)	bis(4,1-phenylene	oxyme	thylene)]bisoxirane		
	oral	LD50 1980 mg/kg	00	Rabbit		Rabbits were orally gavaged with test ma
	dermal	LD50 2300 mg/kg	00		Pre-supplier/manufac turer	
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)					olecular
	oral	LD50 >200 mg/kg	00		Pre-supplier/manufac turer	
	dermal	LD50 >200 mg/kg	00		Pre-supplier/manufac turer	

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000))

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 8 of 13

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method		
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane							
	Acute algae toxicity	ErC50 > 100 mg/l		Raphidocelis subcapitata	, ,	OECD Guideline 201		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No Chemical name					Log Pow		
1675-54-3	1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane						
BCF	BCF						
CAS No	Chemical name	BCF	Species	Source			

CAS No	Chemical name	BCF	Species	Source
1675-54-3	2,2'-	31		Study report (2010)
	[(1-methylethylidene)bis(4,1-phenylene oxymethylene)]bisoxirane			

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Product code: 7418

Page 9 of 13

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(Epoxide Resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(Epoxide Resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(Epoxide Resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420			
Revision date: 21.03.2025	Product code: 7418	Page 10 of 13	
Hazard label:	9		
Special Provisions: Limited quantity: Excepted quantity: EmS:	274 335 969 5 L E1 F-A, S-F		
Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide Resin) 9 III 9		
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo: IATA-max. quantity - Cargo:	⁹ A97 A158 A197 A215 30 kg G Y964 E1 964 450 L 964 450 L		
ENVIRONMENTALLY HAZARDOUS:	Yes		
Danger releasing substance: <u>14.6. Special precautions for user</u> No information available. <u>14.7. Maritime transport in bulk according</u>	Epoxide Resin		

not applicable

Other applicable information

ADR: 375: These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG: 2.10.2.7: Marine pollutants in individual packaging or composite packaging with a net quantity per individual or inner packaging of no more than 5 L for liquids or a net mass per individual or inner packaging of no more than 5 kg for solids are not subject to any other provisions of this Code applicable to marine pollutants, provided that the packaging complies with the general Meet the requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants that also meet the criteria for inclusion in another class, all provisions of this Code that apply to any further hazards continue to apply.

IATA: A197 (375): These substances when transported in single or combination packagings containing a net



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 11 of 13

quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU	regulatory	information
----	------------	-------------

Restrictions on use (REACH, annex XVII): Entry 75	
Information according to Directive 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 12 of 13

Abbreviations and acronyms Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation Aquatic Chronic: Chronic aquatic hazard CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations** CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) IMDG: International Maritime Code for Dangerous Goods EmS: Emergency Schedules MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 21.03.2025

Product code: 7418

Page 13 of 13

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)